

## ALPIMATIC

# Standard type

- Nominal voltage 400 V 50 Hz Three-phase
- Max 470 V

Cat. Nos	Nominal power (kvar)	Electrical Steps (kvar)	Dimensions	Weight
			(mm)	(kg)
			W x D x H	
M 1040	10	2 x 5	260 x 320 x 650	40
M 1540	15	3 x 5	260 x 320 x 650	40
M 2040	20	2 x 10	260 x 320 x 650	40
M 2540	25	2,5 x 10	260 x 320 x 650	40
M 3040	30	3 x 10	260 x 320 x 650	45
M 3540	35	7 x 5	260 x 320 x 650	45
M 4040	40	4 x 10	260 x 320 x 650	45
M 5040	50	5 x 10	260 x 320 x 650	45
M 6040	60	3 x 20	260 x 320 x 770	50
M 7540	75	3 x 25	260 x 320 x 770	75
M 87.540	87,5	7 x 12,5	350 x 500 x 1000	80
M 10040	100	4 x 25	350 x 500 x 1000	80
M 12540	125	5 x 25	350 x 500 x 1000	90
M 15040	150	6 x 25	600 x 500 x 1400	125
M 17540	175	7 x 25	600 x 500 x 1400	140
M 20040	200	4 x 50	600 x 500 x 1400	150
M 22540	225	9 x 25	600 x 500 x 1400	160
M 25040	250	5 x 50	600 x 500 x 1400	170
M 27540	275	11 x 25	600 x 500 x 1400	190
M 30040	300	12 x 25	600 x 500 x 1400	200
M 35040	350	7 x 50	600 x 500 x 1900	260
M 40040	400	8 x 50	600 x 500 x 1900	290
M 45040	450	6 x 75	600 x 500 x 1900	300
M 50040	500	10 x 50	1200 x 500 x 1400	370
M 55040	550	11 x 50	1200 x 500 x 1400	400
M 60040	600	8 x 75	1200 x 500 x 1400	430
M 67540	675	9 x 75	1200 x 500 x 1900	490
M 75040	750	10 x 75	1200 x 500 x 1900	500
M 82540	825	11 x 75	1200 x 500 x 1900	540
M 90040	900	12 x 75	1200 x 500 x 1900	560