

Gamme ALPISTATIC

Type SAH

- Tension nominale 400 V 50 Hz TRI

→ Version classique – Max 470 V

Référence	Puissance nominale (kvar)	Régulation	Dimensions	Poids
		(kvar)	L x P x H (mm)	(kg)
STS10040.215	100	4 X 25	800 x 500 x 1900	210
STS12540.215	125	5 X 25	800 x 500 x 1900	240
STS15040.215	150	3 X 50	800 x 500 x 1900	280
STS17540.215	175	3,5 X 50	800 x 500 x 1900	300
STS20040.215	200	4 X 50	800 x 500 x 1900	320
STS22540.215	225	9 X 25	800 x 500 x 1900	360
STS25040.215	250	5 X 50	800 x 500 x 1900	380
STS27540.215	275	5,5 X 50	800 x 500 x 1900	400
STS30040.215	300	6 X 50	800 x 500 x 1900	430
STS35040.215	350	7 X 50	800 x 500 x 1900	460
STS40040.215	400	4 X 100	800 x 500 x 1900	500
STS45040.215	450	6 X 75	1000 x 600 x 2100	530
STS50040.215	500	4 X 125	1000 x 600 x 2100	630
STS52540.215	525	7 X 75	2000 x 600 x 2100	660
STS57540.215	575	75 + 4X125	2000 x 600 x 2100	690
STS62540.215	625	5 X 125	2000 x 600 x 2100	720
STS70040.215	700	75 + 5X125	2000 x 600 x 2100	780
STS75040.215	750	6 X 125	2000 x 600 x 2100	810
STS82540.215	825	11 X 75	2000 x 600 x 2100	840
STS87540.215	875	7 X 125	2000 x 600 x 2100	870
STS95040.215	950	75 + 7 X125	2000 x 600 x 2100	910
STS100040.215	1000	8 X 125	2000 x 600 x 2100	930
STS112540.215	1125	9 X 125	3000 x 600 x 2100	1000
STS125040.215	1250	10 X 125	3000 x 600 x 2100	1100
STS137540.215	1375	11 X 125	3000 x 600 x 2100	1200
STS150040.215	1500	12 X 125	3000 x 600 x 2100	1300

→ Version renforcée – Max 520 V

Référence	Puissance nominale (kvar)	Régulation	Dimensions	Poids
		(kvar)	L x P x H (mm)	(kg)
STS.R12040.215	120	3 x 40	800 x500 x 1900	250
STS.R16040.215	160	4 x 40	800 x500 x 1900	280
STS.R20040.215	200	5 x 40	800 x500 x 1900	320
STS.R24040.215	240	6 x 40	800 x500 x 1900	360
STS.R28040.215	280	7 x 40	800 x500 x 1900	400
STS.R32040.215	320	4 x 80	800 x500 x 1900	430
STS.R36040.215	360	9 x 40	800 x 500 x 2100	460
STS.R40040.215	400	5 x 80	800 x 500 x 2100	500
STS.R44040.215	440	5,5 x 40	1000 x 600 x2100	530
STS.R48040.215	480	4 x 120	1000 x 600 x2100	630
STS.R52040.215	520	6,5 x 80	2000 x 600 x 2100	660
STS.R56040.215	560	7 x 80	2000 x 600 x 2100	690
STS.R60040.215	600	5 x 120	2000 x 600 x 2100	720
STS.R68040.215	680	8,5 x 80	2000 x 600 x 2100	780
STS.R72040.215	720	6 x 120	2000 x 600 x 2100	810
STS.R80040.215	800	10 x 80	2000 x 600 x 2100	850
STS.R84040.215	840	7 x 120	2000 x 600 x 2100	900
STS.R92040.215	920	11,5 x 80	2000 x 600 x 2100	930
STS.R96040.215	960	8 x 120	2000 x 600 x 2100	950
STS.R108040.215	1080	9 x 120	3000 x 600 x 2100	1000
STS.R120040.215	1200	10 x 120	3000 x 600 x 2100	1100
STS.R132040.215	1320	11 x 120	3000 x 600 x 2100	1200
STS.R144040.215	1440	12 x 120	3000 x 600 x 2100	1300

→ Version sur-renforcée – Max 620 V

Référence	Puissance nominale (kvar)	Régulation	Dimensions	Poids
		(kvar)	L x P x H (mm)	(kg)
STS.RS.14440.215	144	2 X 72	1000 X 600 X 2100	350
STS.RS.21640.215	216	3 X 72	1000 x 600 X 2100	430
STS.RS.28840.215	288	4 X 72	1000 X 600 X 2100	510
STS.RS.36040.215	360	5 X 72	1000 X 600 X 2100	650
STS.RS.43240.215	432	6 X 72	1000 X 600 X 2100	730
STS.RS.50440.215	504	7 X 72	1000 X 600 X 2100	810
STS.RS.57640;215	576	8 X 72	1000 X 600 X 2100	870
STS.RS.64840.215	648	9 X 72	3000 x 600 x 2100	1000
STS.RS.72040.215	720	10 X 72	3000 x 600 x 2100	1180
STS.RS.79240.215	792	11 X72	3000 x 600 x 2100	1250
STS.RS.86440.215	864	12 X 72	3000 x 600 x 2100	1310